

## Catalog Number

47451-W-01-005

**Adapter**, for use with low to medium pressure HPLC. Waters female to 10-32 male connection, 0.40 mm / 0.016 bore size. Natural PEEK. ARE-Applied Research brand. 5/PK.



### Additional Info

This finger tightened adapter makes changing from Waters® to more common connections very convenient. This all-PEEK adapter has a Waters® style female screw threaded port on one side and a standard 10-32 screw threaded male connector with a built-in ferrule with a "universal" pilot length.

- Maximum Temperature: 100°C
- Maximum Pressure: 8,000 psig.
- Click [HERE](#) for economical pack of 10.

The "flat" section on the knurled adapter allows to use a wrench for an extra 1/8 of clockwise turn for tighter sealing or a slight counterclockwise turn to help remove if a tight fitting is too hard for hand removal. The flat section can also be used to hold the adapter in place with a wrench while the Waters male nut is tightened in the adapter.

### MicroSolv Technology Corporation

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: [customers@mtc-usa.com](mailto:customers@mtc-usa.com)

Website: [www.mtc-usa.com](http://www.mtc-usa.com)

### Price

**\$313.46**

Printed On 2024/05/20