


Catalog Number

49225-65-1C

Tubing, PTFE, 1/16th inch (1.6 mm) ID, 1/8th inch (3.2 mm) OD, low pressure, Your custom continuous length Tubing, priced per meter. ARE-Applied Research brand.



Additional Info

You determine the length of this thin walled PTFE (*Polytetrafluoroethylene*) tubing that is extruded from virgin PTFE. No additives are added to the original PTFE material.

This tubing is used widely in all low-pressure, laboratory applications including before and after an HPLC Pump such as with Mobile Phase Delivery and Solvent Waste Systems. Since PTFE tubing contains "micro-pores" in the tubing wall, which allows a quick air exchange, consideration for use with degassed and oxygen-sensitive solvents is needed.

- Internal and Outer Dimensional Tolerance: +/- 0.20mm
- Color: Natural, Translucent
- Wall Thickness; 0.80 mm
- Pressure rating: 510 psi (35 bar)
- Max Temperature: 260°C
- Lengths of 15 m or longer supplied on a convenient spool.

MicroSolv Technology Corporation

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: customers@mtc-usa.com

Website: www.mtc-usa.com

Printed On 2024/05/20