

Fosetyl aluminum analysis by Reversed Phase HPLC Bidentate C18 - Tips & Suggestions

Reversed Phase or Aqueous Normal Phase ANP method tips:

You can use the Cogent Bidentate C18[™] column in Reversed Phase (*RP*) with a high water content method. According to a 2014 third-party research article, if the analysis is done by reversed phase an ion pair agent is recommended to increase retention and reduce peak tailing. Here, 8 mM sodium sulfate was used in a pH 4.3 phosphate <u>buffer</u> mobile phase. Cogent[™] columns work well with ion pair agents and will not be degraded. Also, the Bidentate C18[™] is more hydrophobic than other columns on the market due to the Cogent TYPE-C Silica[™] surface. Therefore you may obtain higher retention for this highly polar <u>analyte</u>.

As for detection methods, it was reported that direct detection with a UV detector can be achieved by the addition of a KOH solution to the sample. In this case, a narrow absorbance <u>band</u> was observed with λ_{max} at 200 nm. Indirect detection could also be used; in this case, you add a UV absorbing compound in the mobile phase and obtain a negative peak.

NOTE: If you try the method by Aqueous Normal Phase ANP, we suggest the C<u>ogent Diamond HydrideTM column.</u> You will want to omit the ion pair agent in this case and use a high percent of acetonitrile in the mobile phase to obtain retention.



Printed from the Chrom Resource Center
Copyright 2025, All Rights Apply
MicroSolv Technology Corporation
9158 Industrial Blvd. NE, Leland, NC 28451

Tel: (732) 380-8900 Fax: (910) 769-9435

Email: customers@mtc-usa.com

Website: www.mtc-usa.com