

Inorganic Buffers Use for HPLC UV Analysis of Citric Acid - Tips & Suggestions

Date: 17-DECEMBER-2015 Last Updated: 1-DECEMBER-2025

If you must use UV detection, the best option would be to use a phosphate <u>buffer</u> that has a pH slightly less than 7.0 (~6.6 or 6.7 should be suitable). You can use a combination of mono and dibasic phosphates to achieve this. You want citric acid to be completely ionized to maximize retention in the ANP mode.

There are a few precautions to consider with phosphates. Some data has suggested that use of phosphates may alter the column chemistry so if they are used, the column should be thereafter dedicated to that application. Also, it is important to know that the column must be only used with UV and **not** in any LC-MS application because phosphates are incompatible with MS.

NOTE: If you can use LCMS, the ideal choice would be a mobile phase based on ammonium acetate or formate, such as the one described in the following application note: <u>Citric Acid Application Note</u>

Cogent Diamond Hydride HPLC Column Ordering Information



Printed from the Chrom Resource Center
Copyright 2025, All Rights Apply
MicroSolv Technology Corporation
9158 Industrial Blvd. NE, Leland, NC 28451

Tel: (732) 380-8900 Fax: (910) 769-9435

Email: customers@mtc-usa.com

Website: www.mtc-usa.com