


Catalog Number

47240-30

Tubing, PTFE, 0.030 inch (0.75 mm) ID, 1/16th inch (1.6 mm) OD, low pressure, green, 5 meter roll, ARE-Applied Research brand. 1 EA.



Additional Info

This PTFE (*Polytetrafluoroethylene*) tubing is extruded from virgin PTFE. No additives are added to the original PTFE material, except for particles for color coding.

This tubing is used widely in all low-pressure, laboratory applications including before and after an HPLC Pump such as with Mobile Phase Delivery and Solvent Waste Systems. Since PTFE tubing contains "micro-pores" in the tubing wall, which allows a quick air exchange, consideration for use with degassed and oxygen-sensitive solvents is needed.

Price
\$29.54

Additional Info

- Internal and Outer Dimensional Tolerance: +/- 0.10mm
- Color: Green
- Wall Thickness: 0.425 mm
- Pressure rating: 510 psi (35.1 bar)
- Max Temperature: 260°C

NOTE: *This item is in compliance with the RoHS EU Directive 2011/65/EU and its amendment (EU) 2015/863 regarding the restriction of hazardous substances.*

Other lengths available:

- [1 meter roll](#)
- [3 meter roll](#)
- [10 meter roll](#)
- [25 meter roll](#)

Custom cuts also available. Please contact [Customer Service](#).

MicroSolv

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: customers@mtc-usa.com

Website: www.mtc-usa.com

Price

\$29.54