

Catalog Number

47451-12-005

Adapter, for use with low to medium pressure HPLC. 1/4-28 female to female Luer connection, 1.3 mm / 0.051 bore size. PEEK. ARE-Applied Research brand. 5/PK.



Additional Info

These wider bore, all-PEEK adapters have one side with a 1/4-28 threaded female port, and the other side is a female Luer slip connection.

These easy to install adapters are great tools for priming HPLC instruments through the prime purge valve with a syringe.

- Maximum Temperature: 100°C.
- Maximum Pressure: 8,000 psig.
- Click [HERE](#) for economical pack of 10.

Price
\$87.29



Additional Info

- Click [HERE](#) for 10-32 Female threaded adapter.

The "flat" section on the knurled adapter allows to use a wrench for an extra 1/8 of clockwise turn for tighter sealing or a slight counterclockwise turn to help remove if a tight fitting is too hard for hand removal. The flat section can also be used to hold the adapter in place with a wrench while the male nut is tightened in the adapter.

Note: Click [HERE](#) for key differences between high and low pressure unions and adapters.

MICROSOLV

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: customers@mtc-usa.com

Website: www.mtc-usa.com

Price

\$87.29