

# Catalog Number

47451-51-010

**Adapter**, for use with low to medium pressure HPLC. 10-32 female to M6 male connection, 0.40 mm / 0.016 bore size. PEEK. ARE-Applied Research brand. 10/PK.



## Additional Info

This all-PEEK adapter is great for low to medium pressures and has a 10-32 threaded female port on one side and a European style M6 male screw thread connector on the other side.

- Maximum Temperature: 100°C
- Maximum Pressure: 8,000 psig.
- Click [HERE](#) for pack of 5.

The "flat" section on the knurled adapter allows to use a wrench for an extra 1/8 of

**Price****\$124.94**

## Additional Info

clockwise turn for tighter sealing or a slight counterclockwise turn to help remove if a tight fitting is too hard for hand removal. The flat section can also be used to hold the adapter in place with a wrench while the male nut is tightened in the adapter.

Note: Click [HERE](#) for key differences between high and low pressure unions and adapters.

### MicroSolv

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: [customers@mtc-usa.com](mailto:customers@mtc-usa.com)

Website: [www.mtc-usa.com](http://www.mtc-usa.com)

### Price

**\$124.94**