


Catalog Number

49210-70-1M

Tubing, PTFE, 0.066 inch (1.7 mm) ID, 0.080 inch (2 mm) OD, low pressure, 1 meter roll, ARE-Applied Research brand. 1 EA.



Additional Info

This thin walled PTFE (*Polytetrafluoroethylene*) tubing is extruded from virgin PTFE. No additives are added to the original PTFE material, except for particles for color coding.

This tubing is used widely in all low-pressure, laboratory applications including before and after an HPLC Pump such as with Mobile Phase Delivery and Solvent Waste Systems. Since PTFE tubing contains "micro-pores" in the tubing wall, which allows a quick air exchange, consideration for use with degassed and oxygen-sensitive solvents is needed.

- Internal and Outer Dimensional Tolerance: +/- 0.20mm
- Color: Natural, Translucent
- Wall Thickness: 0.15 mm
- Pressure rating: 150 psi (10.3 bar)
- Max Temperature: 260°C
- *Caution Note: This tubing has very thin walls and is easily damaged. Handle with care to*

MicroSolv Technology Corporation

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: customers@mtc-usa.com

Website: www.mtc-usa.com

Price

\$11.71

Printed On 2024/07/27