


Catalog Number

49225-65

Tubing, PTFE, 1/16th inch (1.6 mm) ID, 1/8th inch (3.2 mm) OD, low pressure, 5 meter roll, ARE-Applied Research brand. 1 EA.



Additional Info

This thin-walled PTFE (*Polytetrafluoroethylene*) tubing is extruded from virgin PTFE. No additives are added to the original PTFE material.

This tubing is used widely in all low-pressure, laboratory applications including before and after an HPLC Pump such as with Mobile Phase Delivery and Solvent Waste Systems. Since PTFE tubing contains "micro-pores" in the tubing wall, which allows a quick air exchange, consideration for use with degassed and oxygen-sensitive solvents is needed.

Price
\$33.70

Additional Info

- Internal and Outer Dimensional Tolerance: +/- 0.20mm
- Color: Natural, Translucent
- Wall Thickness; 0.80 mm
- Pressure rating: 510 psi (35 bar)
- Max Temperature: 260°C

Other lengths available:

- [1 meter roll](#)
- [3 meter roll](#)
- [10 meter roll](#)
- [25 meter roll](#)
- [Custom length](#)

MicroSolv

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: customers@mtc-usa.com

Website: www.mtc-usa.com

Price

\$33.70