

Catalog Number

58045-R25-K

Syringe Filters, 25mm, Regenerated Cellulose (RC), 0.45um Pore Size. Brown Polypropylene, AQ Brand. 1000/CS.



Additional Info

Advanced Quality Regenerated Cellulose Syringe Filters, AQ™ brand, for Pharmaceutical Grade HPLC & Dissolution Testing. Manufactured with a unique 0.45µm Regenerated Cellulose Membrane in a 25mm polypropylene housing. These syringe filters are made for laboratories that require consistent, high performance results with ease of use especially during high volume work. Excellent choice when laboratories cannot afford poor chromatographic results.

These filters are used for filtration and sterilization of protein solutions, culture media and buffers. The low protein binding characteristics make these ideal for these types of applications, particularly where the sample size is very small and recovery of protein of interest is sought. Regenerated Cellulose filters provide absolute retention, very low hold up volumes

MicroSolv Technology Corporation

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: customers@mtc-usa.com

Website: www.mtc-usa.com

Price

\$2,529.41

Printed On 2024/08/06

Additional Info

and low protein binding while offering excellent throughputs. Do not use these filters with strong Acids or Bases.

Validated for many regulatory requirements they are Designed, Tested and QC Certified. They comply with US FDA CFR Title 21, Part 211.92 for minimum Fiber Release and with USP <788> test for particulate matter in injectables as well as USP for "Sterile Water for Injection" and therefore do not require any initial flushing or discarding of the first 200µl of filtrate saving time and avoiding investigation of failed methods. The polypropylene plastic housing material complies with the requirements of US FDA CFR Title 21 Part 177.1520 and are heat sealed to prevent leaching. These filters pass a test for oxidizable matter as per the USP.

Color Coded: Brown for 0.45µm Regenerated Cellulose, these filters can be autoclaved for 0.5 hours at 121°C, 0.1MPa or with ethylene oxide.

Click [HERE](#) for Product Specifications, Click [HERE](#) for 100 in a package quantity or Click [HERE](#) for 50 in a package quantity.

MicroSolv Technology Corporation
9158 Industrial Blvd. NE, Leland, NC 28451
tel. (732) 380-8900, fax (910) 769-9435
Email: customers@mtc-usa.com
Website: www.mtc-usa.com

Price
\$2,529.41

Printed On 2024/08/06